# FS-10 Polyester Base Film Carrier Sheet

With the introduction of new press technology print capabilities have increased rendering higher press speeds than ever before. Many of these new advancements require a much smaller undercut therefore trade shops must provide plate mounts that provide reduced plate thickness and mounting blanket thickness.

FS-10 and FS-14 is a High impact Grade Polyester Base Mounting

Film and is available in white opaque and clear finishes.

#### Features:

- · Custom roll length and width available
- High Grade Polyester very durable

#### Roll Material Spec's:

#### FS-10 Polyester Film high grade print carrier

Standard Roll Length at 100'

Standard Roll Width: 27" 36" 39" 60" 62" 74"

Thickness: .010 in 10 mil. (.25 mm)

Thickness Tolerance: Variation within individual roll = to +/- .001 in.

Color: White Core Size: 3" O.D.

\* Custom slit widths available call for price and stock request.

### FS-10C Polyester Film high grade print carrier

Standard Roll Length at 100'

Standard Roll Width: 44" 68" 74" Thickness: .010 in 10 mil. (.25 mm)

Thickness Tolerance: Variation within individual roll = to +/- .001 in.

Color: Clear Core Size: 3" O.D.

\* Custom slit widths available call for price and stock request.

### FS-14 Polyester Film high grade print carrier

Standard Roll Length at 100'

Standard Roll Width: 48" 60" 64.125" 65.5"

Thickness: .014 in 14 mil. (.35mm)

Thickness Tolerance: Variation within individual roll = to +/- .001 in.

Color: White Opaque Core Size: 3" O.D.

\* Custom slit widths available call for price and stock request.

# FS-5PF 5 mil. Matte Polyester Film for digital ink proofing systems & pen and ink plotter systems

#### Features:

- Exceptional ink coverage/Reception
- Age Resistant, Acid Neutral Low Light Diffraction Film
- High Resolution

## Roll Material Spec's:

Standard Roll Length at 108' Standard Roll Width: 48" Standard Roll Length at 300' Standard Roll Width:

Thickness: .005 in.

Thickness Tolerance: Variation within individual roll = to  $\pm$ -.001 in. Core Size: 3" O.D.

\* Custom slit widths available call for price and stock request.



